

RG仁公气动双隔膜常用型号及一般应用 RenGongpneumatic diaphragm pumps models and the general application

常用型号 General modes	浸液部件 Wetted parts	阀座 Valve seat	球阀 Valve ball	隔膜 Diaphragm	一般应用 Common use
RG06 1/4in(6.35mm)出口outlet 最大流量值 Max flow:17 lpm(1.02 m³/h)					
RG06MMMF	Acetal	Acetal	Acetal	PTEE	清洗用溶剂 Cleaning solvent
RG06PPPF	Poly	Poly	Poly	PTEE	清洗用中性流体 Cleaning neutral liquid
RG06KKF	PVDF	PVDF	PVDF	PTEE	高温度高浓度的酸碱：干净的氢氟酸和盐酸 High-temperature, high-concentration acid & alkali, clean HF, HCl
RG10 3/8in(9.25mm)出口outlet 最大流量值 Max flow:26 lpm(1.56 m³/h)					
RG10MMHH	Acetal	Acetal	Hytrel	Hytrel	中等PH值的溶剂和溶剂型涂料：水，油等 Medium PH of the solvent and solvent-based paint: water, oil etc.
RG10MMFF	Acetal	Acetal	PTFE	PTFE	低固体颗粒，涂料，染料，清漆 Low solid particles, paint, varnish
RG10PPFF	Poly	Poly	PTFE	PTFE	不含研磨材料-硫酸和硝酸，所有PH值的酸碱类流体 Non abrasive materials-pure H2SO4, HNO3, all acids & alkali liquid
RG10PPPTT	Poly	Poly	Santoprene	Santoprene	在温度和酸性不强的场合替代PFF In the case of normal temperature and acidity it can replace PFF
RG10PPHH	Poly	Poly	Hytrel	Hytrel	适用于水和其他中性无溶剂流体，水性涂料，粘合剂 Apply to water and other neutral fluids, water-based paints, adhesives
RG15 1/2in(12.7mm)出口outlet 最大流量值 Max flow:50lpm(3.0 m³/h)					
RG15MMFF	Acetal	Acetal	PTFE	PTFE	溶剂和溶剂性涂料 Solvent and solvent-based paint
RG15MSFF	Acetal	SST	PTFE	PTFE	可用于强酸强碱的流体，溶剂性涂料 Apply to strong acids & strong alkali, etc and solvent-based paint
RG15PPFF	Poly	Poly	PTFE	PTFE	不含研磨材料-硫酸和硝酸，所有PH值的酸碱类流体 Non abrasive materials-pure H2SO4, HNO3, all acids & alkali liquid
RG15PPTT	Poly	Poly	Santoprene	Santoprene	在温度和酸性不强的场合替代PFF In the case of normal temperature and acidity it can replace PFF
RG15KKFF	PVDF	PVDF	PTFE	PTFE	高温度高浓度的酸碱，磨蚀性和腐蚀性流体 High-temperature, high concentration acid & alkali, corrosive and abrasive fluids

常用型号 General models	浸液部件 Wetted parts	阀座 Valve seat	球阀 Valve ball	隔膜 Diaphragm	一般应用 Common use
RG15 3/4in(19.0mm)出口outlet 最大流量值 Max flow:50lpm(3.0 m³/h)					
RG20AMFF	Al	Acetal	PTFE	PTFE	溶剂和溶剂性涂料 Solvent and solvent-based paint
RG20AMBB	Al	Acetal	Buna	Buna	清洗用中性流体 Cleaning neutral liquid
RG20ASFF	Al	SST	PTFE	PTFE	可用于强酸强碱的流体, 溶剂性涂料 Apply to strong acids & strong alkali, etc and solvent-based paint
RG20SSFF	SST	SST	PTFE	PTFE	可用于强酸强碱的流体, 水性涂料 Apply to strong acids & strong alkali, etc and water-based paint
RG20SSSF	SST	SST	SST	PTFE	高粘度, 普通酸碱, 高固份水性涂料 High-viscosity, common acid & alkali, high-solid water-based paint
RG25 1in(150mm)出口outlet 最大流量值 Max flow:150lpm(9.0m³/h)					
RG25PPFF	Poly	Poly	PTFE	PTFE	不含研磨材料-硫酸和硝酸, 所有PH值的酸碱类流体 Non abrasive materials-pure H2SO4, HNO3, all acids & alkali liquid
RG25PPTT	Poly	Poly	Santoprene	Santoprene	在温度和酸性不强的场合替代PFF In the case of normal temperature and acidity it can replace PFF
RG25AHMH	Al	Hytrel	Acetal	Hytrel	适用于中性流体, 水, 油, 挡风玻璃清洗液 Apply to the neutral fluid, water, oil, windshield washing fluid
RG25AGGG	Al	Geolast	Geolast	Geolast	中性PH值的含有研磨材料的石油产品, 水性涂料 Neutral PH, petroleum products with abrasive materials, water-based paint
RG25ASFF	Al	SST	PTFE	PTFE	可用于强酸强碱的流体, 溶剂性涂料 Apply to strong acids & strong alkali, etc and solvent-based paint
RG25SSFF	SST	SST	PTFE	PTFE	可用于强酸强碱的流体, 水性涂料 Apply to strong acids & strong alkali, etc and water-based paint
RG25KKFF	PVDF	PVDF	PTFE	PTFE	高温高浓度的酸碱, 磨蚀性和腐蚀性流体 High-temperature, high concentration acid & alkali, corrosive and abrasive fluids
RG40 1.5in(40.58mm)出口outlet 最大流量值 Max flow:340lpm(20m³/h)					
RG40PPFF	Poly	Poly	PTFE	PTFE	不含研磨材料-硫酸和硝酸, 所有PH值的酸碱类流体 Non abrasive materials-pure H2SO4, HNO3, all acids & alkali liquid
RG40PPTT	Poly	Poly	Santoprene	Santoprene	在温度和酸性不强的场合替代PFF In the case of normal temperature and acidity it can replace PFF
RG40AHMH	Al	Hytrel	Acetal	Hytrel	适用于中性流体, 水, 油, 挡风玻璃清洗液 Apply to the neutral fluid, water, oil, windshield washing fluid
RG40SGGG	Al	Geolast	Geolast	Geolast	中性PH值的含有研磨材料的石油产品, 水性涂料 Neutral PH, petroleum products with abrasive materials, water-based paint
RG40ASFF	Al	SST	PTFE	PTFE	可用于强酸强碱的流体, 溶剂性涂料 Apply to strong acids & strong alkali, etc and solvent-based paint
RG40SSFF	SST	SST	PTFE	PTFE	可用于强酸强碱的流体, 水性涂料 Apply to strong acids & strong alkali, etc and water-based paint
RG40KKFF	PVDF	PVDF	PTFE	PTFE	高温高浓度的酸碱, 磨蚀性和腐蚀性流体 High-temperature, high concentration acid & alkali, corrosive and abrasive fluids

常用型号 General modes	浸液部件 Wetted parts	阀座 Valve seat	球阀 Valve ball	隔膜 Diaphragm	一般应用 Common use
R_Q50 2in(50.8mm)出口outlet 最大流量值 Max flow:570lpm(34m ³ /h)					
R _Q 50PPFF	Acetal	Acetal	Acetal	PTFE	不含研磨材料-硫酸和硝酸，所有PH值的酸碱类流体 Non abrasive materials-pure H2SO4,HNO3,all acids & alkali liquid
R _Q 50PPTT	Poly	Poly	Santoprene	Santoprene	在温度和酸性不强的场合替代PFF In the case of mormal temperature and ciditya it can replace PFF
R _Q 50AHMH	Al	Hytrel	Acetal	Hytrel	适用于中性流体，水，油，挡风玻璃清洗液 Apply to the neutral fluid, water, oil, windshield washing fluid
R _Q 50ASFF	Al	SST	PTFE	PTFE	可用于溶剂性涂料 Apply to stror g acids & strong alkali,etc and solvent-based paint
R _Q 50AGGG	Al	Geolast	Geolast	Geolast	中性PH值的含有研磨材料的石油产品，水性涂料 Neutral PH, petroleum products with abrasive materials, water-based paint
R _Q 50SSFF	SST	SST	PTFE	PTFE	可用于强酸强碱的流体，溶剂性涂料 Apply to strong acids & strong alkali,etc and solvent-based paint
R _Q 50STTT	SST	Santoprene	Santoprene	Santoprene	可用于强酸强碱的流体，水性涂料 Apply to strong acids & strong alkali,etc and water-based paint
R _Q 50KKFF	PVDF	PVDF	PTFE	PTFE	高温度高尝试的酸碱，磨蚀性和腐蚀性流体 High-temperature, high concentration acid & alkali, corrosive and abrasive fluids
R_Q80 3in(76.2mm)出口outlet 最大流量值 Max flow:1000 lpm(60m ³ /h)					
R _Q 80AGGG	Al	Geolast	Geolast	Geolast	中性PH值的含有研磨材料的石油产品，水性涂料 Neutral PH, petroleum products with abrasive materials, water-based paint
R _Q 80AHMS	Al	Hytrel	Acetal	Hytrel	适用于中性流体，水，油，挡风玻璃清洗液 Apply to the neu tral fluid, water, oil, windshield washing fluid
R _Q 80ATTT	Al	Santoprene	Santoprene	Santoprene	适用于无溶剂，中等PH值的流体 Apply to non-solvent fluid, the fluid of medium PH
R _Q 80ASFF	Al	SST	SST	SST	PTFE可用于强酸强碱的流体，溶剂性涂料 Apply to strong acids & strong alkali,etc and solvent-based paint

常用型号 General models	浸液部件 Wetted parts	阀座 Valve seat	球阀 Valve ball	隔膜 Diaphragm	一般应用 Common use
R _Q XAHHM	Al	Hytrel	Acetal	Hytrel	适合输送 水、油、酒精等中性介质 Apply to the neutral fluid, water, oil, windshield washing fluid
R _Q XASFF	Al	SST	PTFE	PTFE	适合输送较强磨蚀性的溶剂 Apply to strong acids & strong alkali, etc and solvent-based paint
R _Q DXPPFF	Poly	Poly	PTFE	PTFE	适合输送盐酸、硫酸、碱液等强氧化性介质（PTT也可） Non abrasive materials-pure H2SO4, HNO3, all acids & alkali liquid
R _Q XSSFF	SST	SST	PTFE	PTFE	适合输送浓硫酸、硝酸等强氧化性的介质 Apply to strong acids & strong alkali, etc and water-based paint
R _Q XKKFF	PVDF	PVDF	PTFE	PTFE	化学适应性最好，适合输送几乎所有的流体 High-temperature, high concentration acid & alkali, corrosive and abrasive fluids
R _Q XXMFF		Acetal	PTFE	PTFE	低固体的涂料，着色剂和清漆，溶剂（采用AL\SST或导电乙醚的流体腔） Low solid particles, paint, varnish (Al/Groundable Acetal fluid cavity.)
R _Q XXSSF		SST	SST	SST	适用于普通酸碱，含有研磨材料的亚滤料，磨蚀性的淤泥，矿泥等 High-viscosity, common acid & alkali, high-solid water-based paint
R _Q XXSFF		SST	PTFE	PTFE	可用于强酸强碱的流体 Apply to strong acids & strong alkali, etc
R _Q XXHMH		Hytrel	Acetal	Acetal	适用于中性流体，水，油，挡风玻璃清洗液 Apply to the neutral fluid, water, oil, windshield washing fluid
RDXXGGG		Geolast	Geolast	Geolast	中性PH值的含有研磨材料的石油产品，地表输送 Neutral PH, petroleum products with abrasive materials, water-based paint and the delivery of surface water
R _Q XXSTT		SST	Santoprene	Santoprene	普通酸碱，含有研磨材料的皂液，清洗化学品，压滤液，不适用于溶剂 Common acid & alkali, the soap liquid with abrasive materials, cleaning chemicals, pressure filtration, not suitable for solvent.
R _Q XXPHH		PP	Hytrel	Hytrel	适用于水和其他中性无溶剂流体，水性涂料，粘合剂 Apply to water and other neutral fluids, water-based paints, adhesives
R _Q XXPFF		PP	PTFE	PTFE	最佳的低成本抗化学品组合，具有广泛的适用性 The best combination of low-cost, anti-chemicals, widely used
R _Q XXSW		SST	Viton	Viton	无铅汽油和电镀化学液 Unleaded petrol and electroplating chemical solution
R _Q XXKW		PVDF	Viton	Viton	电镀化学液 Electroplating chemical solution
R _Q XXKFF		PVDF	PTFE	PTFE	适用于高浓度高温度的酸碱，磨蚀性、腐蚀性的流体 High-temperature, high concentration acid & alkali, corrosive and abrasive fluids